

Effects of Using Dyneema® Fiber Mooring Lines with Wire Rope Mooring Lines

CONVERSION PROCESS

The use of synthetic auxiliary lines, typically polyester fiber, in conjunction with wire rope primary mooring lines have been widely used and accepted provided they are arranged and used symmetrically about the midship. When properly planned and managed, there are times when synthetic fiber mooring lines can be added, and in some cases it even adds additional security. However the combined use of synthetic and wire rope primary mooring lines, a “mixed mooring,” has historically been discouraged due to the large differences in elastic elongations, especially with vessels using fixed brake winches. [1]

With the increased popularity of HMPE synthetic fiber mooring lines that have elastic elongation in the same order of magnitude of traditional wire rope, the issue of mixed moorings has resurfaced. Many vessel operators want to take advantage of the new synthetic technology due to its ergonomics and overall economic value, but do not want to retrofit an entire vessel prior to extensive field trials. The most common solution is to request a single line for trial and to use it in parallel with the existing mooring lines. This practice can still create a dangerous situation if the elongations and breaking strengths are not carefully matched.

SCENARIO 1

Even though high-modulus fiber rope has published elastic elongations similar to the elastic elongation of wire rope, the differences can still be very significant. For example, if a DPX™-75 mooring line is used in a trial with a wire rope as a breast line as shown in the graphic scenario in Fig. 1, the wire rope would see an increased tension (see Table 1 for actual results). This difference would effectively limit the holding power of the mooring system, but would not likely produce catastrophic results immediately. In this instance, the wire rope would fatigue at a much higher rate than the DPX™-75, which over time would create premature failure of the wire rope mooring lines (see Fig. 2). [3]




FIGURE 1 Mooring Schematic [2].

Blue lines represent DPX™-75 and the black lines represent wire rope.

TABLE 1 Line tension comparison for Figure 1.
(Where the total applied load = 150 metric tons)

	Load	% of New Rope Breaking Strength
Line #1 – Wire Rope	44 metric tons	37%
Line #2 – DPX™-75	31 metric tons	25%
Line #3 – DPX™-75	31 metric tons	25%
Line #4 – Wire Rope	44 metric tons	37%




FIGURE 2 Tensile Fatigue Comparison.



Effects of Using Dyneema® Fiber Mooring Lines with Wire Rope Mooring Lines

SCENARIO 2

Changing the position of the high-modulus synthetic fiber lines can minimize the line tension differential. In an actual mooring scheme, the majority of the lines sent ashore are used to restrain a combination of lateral and longitudinal forces as well as yaw moments; therefore this situation will still produce tension differentials between dissimilar material mooring lines. For simplicity, we assume a vessel uses the mooring arrangement in Fig. 3. By placing the synthetic lines side-by-side, the situation is no longer dependant on the overall elastic elongation differences between the wire rope and the synthetic fiber mooring lines. However, this mooring arrangement creates an unbalanced system, where the vessel's stern can be displaced more than the bow (see Table 2).

This is further complicated by combining a new synthetic rope with the existing wire rope. Wire rope, like synthetic fiber rope, will degrade over its lifetime, which will likely affect its strength and the elongation characteristics. The degraded strength and elongation could result in the wire rope taking even more load and fatiguing at an increased rate. Without proper testing of the wire rope mooring lines, the addition of synthetic fiber rope is further discouraged.

SCENARIO 3

Changing out a complete set of lines can effectively minimize the load and elongation differentials that the two previous scenarios described. If the complete set of spring lines is changed to synthetic, the lateral restraining forces will be equally distributed and the resultant elongations will be equal in both directions.

CONCLUSION

Mixed moorings, not including the use of auxiliary or secondary lines, even with high-modulus synthetic fiber ropes can have negative effects on mooring systems and should only be used if testing is performed and the load/elongation characteristics are carefully matched. To successfully implement a change from wire rope mooring lines to HMPE synthetic mooring lines, which many Samson customers have recently done, we recommend contacting our Commercial Marine Sales Division or Application Engineering. Samson has produced detailed information on how to successfully “retro-fit” a vessel from wire to synthetic and achieve safe and long service life from HMPE mooring lines.

REFERENCES

- [1] OCIMF, *Mooring Equipment Guidelines*, Second Edition, 1997.
- [2] OCIMF, *Mooring Equipment Guidelines*, Second Edition, Figure 1.6, page 8, 1997.
- [3] DSM supplied data.




FIGURE 3 Mooring Schematic [2].
Blue lines represent DPX-75 and the black lines represent wire rope.

TABLE 2 Line tension comparison for Figure 3.
(Total applied load = 150 metric tons and 60 m leads)

	Displacement (m)
Line #1 – DPX™75	0.60 m
Line #2 – DPX™75	0.60 m
Line #3 – Wire Rope	0.32 m
Line #4 – Wire Rope	0.32 m